

Product data sheet uvex silv-Air 2312 FFP3 NR D



Product information

Product features	<ul style="list-style-type: none"> • Particle-filtering cup shape mask with exhalation valve • Protection level FFP3 • Ergonomically for smaller faces • Soft material edges for more high wearing comfort • 4-point headband attachment allows an individual and secure fit • Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask • Flexible and adjustable nose clip • Compatible with uvex safety eyewear • Soft sealing lip guarantees a secure, comfortable sealed position of the mask • Mask fulfils the requirements of the dolomite dust test (D)
Materials	<p>Headband: textile</p> <p>Nose clip: aluminum</p> <p>Headband clips: PP</p> <p>Filter / mask: Melt Blown PP, Polyester</p> <p>Sealing lip: PVC foam</p> <p>Valve: ABS</p>
Weight	29 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8732.312	cup shape mask FFP3, white with valve	15 pcs. per box
8752.312	cup shape mask FFP3, white with valve	2 pcs. per bag
8732.310	cup shape mask FFP3, white with valve, standard size	15 pcs. per box

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Woodworking, hard wood, chromium, asbestos (up to 100,000 F/m ²), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
--	--

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.